

MÁY ĐIỀU KHIỂN NHIỆT ĐỘ KHUÔN BẰNG NƯỚC LẠNH AIR COOLED CHILLER- CA series

Feature:

Employing all-new, imported compressor, complete with all-new import certificates. Employing superb imported components, with longer terms of service. High efficiency evaporator and cooling condenser in use, to help save no less than 30% of your power rates. High precision digital display, for the temperature control. Employing two sets of compressors which can be used jointly or independent. (Over C-10) Complete with safety protection and error indication system. Micro-processing controller, easy operation. The weld of brass pipe is non-oxidization (nitrogen flushing). OEM/ODM Product Branded Product Buyer's Label Offered

Specification Table:

Model	UNIT	CA-2	CA-5	CA-7	CA-10	CA-15	CA-20	CA-25	CA-30
Control range	°C	8°C ~ 30°C	8°C ~ 30°C	8°C ~ 30°C	8°C ~ 30°C	8°C ~ 30°C	8°C ~ 30°C	8°C ~ 30°C	8°C ~ 30°C
Power	-	3Ø 220V 60Hz (or other)	3Ø 220V 60Hz (or other)	3Ø 220V 60Hz (or other)	3Ø 220V 60Hz (or other)	3Ø 220V 60Hz (or other)	3Ø 220V 60Hz (or other)	3Ø 220V 60Hz (or other)	3Ø 220V 60Hz (or other)
Cooling capacity	BTU / HR (60HZ / 50HZ)	24,000/19,700	60,000/51,700	90,000/74,700	120,000/103,500	180,000/152,800	240,000/202,000	300,000/248,000	360,000/296,000
Comp power	HP	2	5	7-1/2	10 (5 x 2)	15 (7-1/2 x 2)	20 (10 x 2)	25 (12-1/2 x 2)	30 (15 x 2)
Pump power	KW	0.56	0.96	0.96	1.23	1.23	1.9	1.9	2.9
Max. Pump pressure	KG/cm ²	2.5	2.5	2.5	2.6	2.6	2.8	2.8	4.6
Max. Pump flow	L/MIN	66	150	150	200	200	266	266	266
Max. Power supply	KW	2.5	5.3	7.2	10	14.2	18.8	23.6	28.3
Tank capacity	LITER	25	50	50	110	175	175	250	250
Chilling water pipe	INCH	3/4	1-1/4	1-1/4	1-1/2	2	2	2-1/2	2-1/2
Cooling water pipe	INCH	3/4	1-1/4	1-1/4	1-1/2	2	2	2-1/2	2-1/2
L x W x H	CM	108 x 60 x 130	125 x 65 x 140	138 x 85 x 147	158 x 85 x 166	211 x 85 x 172	224 x 90 x 172	251 x 113 x 181	273 x 113 x 181
Weight	Kg	180	340	420	720	860	1,060	1,200	1,400

ADD: 70 Ham Nghi ST, Ben Nghe Ward , District 1, HCMC * Tel: +84-866857814

